

## Key Digital KD-4x4CSA 4x4 HDMI Matrix Switch w De-embedding Analog/Digital Audio

- **Input (Each):** 1 HDMI Connector, Type A, 19 Pin Female
- **Output (Each):** 1 HDMI Connector, Type A, 19 Pin Female; 6-Pin Terminal Block for Analog L/R Output; RCA Jack for Digital Audio Output [follows SPDIF format (IEC 60958 )]
- **Bandwidth:** TMDS bandwidth 10.2 Gb/s
- **DDC Signal (Data):** Input DDC Signal - 5 Volts p-p (TTL)
- **HDMI Video/Audio Signal:** Input Video Signal - 1.2 Volts p-p
- **Wired IR:** modulated IR signal input, 0-5V TTL or -10to +10V, 3.5mm mono female connector with signal on tip
- **Power Supply:** KD-PS12V2A - 12V/2A DC Power Supply, Screw-In Type Connector
- **Regulation:** CE, RoHS, WEEE
- **Rack Mount:** 1U, Full Rack Width (rack ears included)
- **Enclosure:** Black Metal
- **Product Dimensions:** 17.25" x 7.5" x 1.75"
- **Shipping Dimensions:** 21.25" x 13" x 3.5"
- **Product Weight:** 6.5 lb.
- **Shipping Weight:** 8 lb.