

Audio and Video		
Inputs	4x HDMI In: 19-pin type A	
Outputs	4x HDMI Out: 19-pin type A 4x Audio Out: RCA Female Stereo (L/R)	
Audio Formats	Analog: 2ch Analog HDMI: 2ch LPCM Multichannel up to Dolby Atmos and DTS-X	
Video Resolutions (Max)	Video Resolution	HDMI
	1920x1080p @60Hz 12bit	15m/49ft
	1920x1080p @120Hz 12bit	7m/23ft
	3840x2160p @24Hz 10bit 4:2:0 HDR	15m/49ft
	3840x2160p @30Hz 8bit 4:4:4	7m/23ft
	3840x2160p @60Hz 10bit 4:2:0 HDR	5m/16ft
	3840x2160p @60Hz 12bit 4:2:2 HDR	5m/16ft
	4096x2160p @60Hz 8bit 4:2:0	7m/23ft
	4096x2160p @60Hz 8bit 4:4:4	5m/16ft
Supported Standards	DCI RGB HDR HDR10 Dolby Vision up to 60Hz HLG BT.2020 BT.2100	
Maximum Pixel Clock	600MHz	
Communication and Control		
HDMI	HDMI 2.0 HDCP 2.2 EDID Input supports DVI/D and DisplayPort Dual-Mode (DP++) v1.3 with adapter (not included)	
CEC	CEC power triggering Requires CEC compatibility	
IR	1x Front Panel IR Sensor Handheld IR Remote Included 1x IR Ext 3.5mm (1/8in) TRS Stereo	
RS-232	1x RS-232: 9-pin DB9 Female Matrix Control Telnet commands supported	
Ethernet	1x LAN: 8-pin RJ-45 Female 10/100 Mbps auto-negotiating Built-in Web UI IP Control	
Power		
Power Supply	100~240V AC 50/60Hz	
Max Power Consumption	27.5W	
Environmental		
Operating Temperature	32°F ~ 113°F (0°C ~ 45°C) 10% ~ 90%, non-condensing	
Storage Temperature	-4°F to ~ 158°F (-20°C ~ +70°C) 10% ~ 90%, non-condensing	
Maximum BTU	94 BTU/hr	
Dimensions and Weight		
Rack Units/Wall Box	1U	
Height	43.5mm/1.72in	
Width	440mm/17.33in	
Depth	300mm/11.82in	
Weight	3.58kg/7.88lbs	
Regulatory		
Safety and Emission	CE FCC RoHS RCM	