

**High Sec Labs KCRHT20-4TRKIT Cable Kit 4 Host / 1 Console / 1 Power Set HDMI D38999 Rugged**

Dimensions	D 141 x W 330 x H 50 mm [5.5 x 13.0 x 1.9 Inch]
Weight (no blades)	2.2 Kg [4.8 lbs] without cables
Host Input Ports	4 x HDMI (DVI-D compatible) and two USB 2.0 interfaces based on a single female D38999/24WD35PN, Optional Composite video or VGA inputs available
Console ports	HDMI (DVI-D compatible), 2 USB device, optional Remote control via a single male D38999/24WD35SN
Channel Switching	IP 67 compliant green LED illuminated front Panel push Buttons, NVG, dimming options, Remote control connected via Console port
Video modes supported	HDMI up to 4K@30Hz or 2600x1600@60Hz, DVI-D 1920x1200@60Hz
Vibration	MIL-STD-810G Method 514.7 Procedure I Category 20 wheeled Ground Vehicles
Humidity	MIL-STD-810G Method 507.6 Procedure I Table 507.6-I
Altitude	MIL-STD-810G Method 500.6 Procedure I
Immersion	MIL-STD-810G Method 512.6 Procedure I to 3 meters fresh water
Salt Fog	MIL-STD-810G Method 509.6
Blowing Sand	MIL-STD-810G Method 510.6 Procedure II 10.6 to 17.7 g/m3
DC Input	Nominal 28VDC (18V-36V)
Power Compliant	MIL-STD-1275E Compliant
Power Requirements	Max Power Consumption 40W
Safety	UL/cUL60950, EN60950
EMI/EMC	FCC Class B, CE Mark, EN55022B, VCCI
Tests	CE102, CS101, CS114, CS115, CS116, RE102, RE103, CE101
NIAP	PP4 for PSD certified
Tempest	Level A
Standard	MIL-HDBK-216
MTBF	65,000 hours at 40 degrees
Manufactured	
BAA & TAA	Compliant