

Panel

Panel Type	VA
Panel Size	15.0"
Max. Resolution	XGA 1024 x 768
Pixel Pitch	0.297 mm
Brightness	300 cd/m ²
Contrast Ratio	20,000,000:1 (DCR)
Viewing Angle (H/V)	176°/176°
Display Colour	16.2M
Colour Gamut	NTSC 72%
Response Time	5 ms

Frequency

Frequency (H)	24 kHz-83 kHz
Frequency (V)	50 Hz-75 Hz

Signal Input

DisplayPort	x 1
HDMI	1.4 x 1
DVI	24-Pin DVI-D
VGA	15-Pin D-Sub x 1
Composite	BNC x 2
S-Video	4-Pin mini DIN x 1

Signal Output

Composite	BNC x 2
-----------	---------

External Control

RS232 In	2.5 mm Phone Jack
----------	-------------------

Power Requirements	DC 12V 1.5A
On Mode	13W (On)
Standby Mode	< 0.5W
Off Mode	< 0.3W

Glass

Thickness	3.0 mm (0.12")
Reflection Rate	< 1%
Transmission Rate	> 97%
Hardness	> 9H

Operating Conditions

Temperature	0°C-40°C (32°F-104°F)
Humidity	10%-90% (non-condensing)

Storage Conditions

Temperature	-20°C-60°C (-4°F-140°F)
Humidity	5%-95% (non-condensing)

Mounting

VESA FPMPI	Yes (100 x 100 mm & 75 x 75 mm)
------------	---------------------------------

Stand

Tilt	0° to 20°
------	-----------

Security

Kensington Security Slot	Yes
--------------------------	-----

Dimensions

Certifications & Compliance

CB
CE
FCC
RoHS
WEEE
REACH
ICES-003(Issue 7)

Accessories

Supplied

Audio Cable
Power Adaptor
Power Cord
Quick Start Guide
VGA Cable
Warranty Card

Optional Accessories

Ceiling Mount (Landscape only)

CMP-01 + WMK-03

Wall Mount (Landscape only)

PMK-01
WMA-01
WMK-01
WMK-03

Desk mount (Landscape only)

DMC-01
DMC-02D
DMS-01D
ES-02
