

Panel	Panel Type:	LED-Backlit TFT LCD (TN Technology)
	Panel Size:	23.6"
	Max. Resolution:	FHD 1920 x 1080
	Pixel Pitch:	0.272 mm
	Brightness:	300 cd/m ²
	Contrast Ratio:	20,000,000:1 (DCR)
	Viewing Angle (H/V):	170°/160°
	Display Colour:	16.7M
	Response Time:	3 ms
	Surface Treatment:	Anti-Glare Treatment (Haze 25%),2H Hard Coating
Frequency	Frequency (H):	24 kHz-83 kHz
	Frequency (V):	50 Hz-75 Hz
Signal Input	SDI:	BNC x 1
	DisplayPort:	x 1
	HDMI:	1.4 x 1
	DVI:	24-Pin DVI-D
	VGA:	15-Pin D-Sub x 1
	Composite:	BNC x 1
Signal Output	SDI:	BNC x 1
	Composite:	BNC x 1
External Control	RS232 In:	2.5 mm Phone Jack
Other Connectivity	USB:	2.0 x 1 (Service Port)
Audio	Audio In:	Stereo Audio Jack (3.5 mm), Stereo Audio Jack (RCA)
	Internal Speakers:	2W x 2
Power	Power Requirements:	DC 12V, 2.75A
	On Mode:	25W (On)
	Standby Mode:	< 0.5W
	Off Mode:	< 0.5W
Glass	Thickness:	3.0 mm (0.12")
	Reflection Rate:	< 1%
	Transmission Rate:	> 97%
	Hardness:	> 9H
Operating Conditions	Temperature:	0°C-40°C (32°F-104°F)
	Humidity:	10%-90% (non-condensing)
Mounting	VESA FPMPI:	Yes (100 x 100 mm & 75 x 75 mm)

Stand	Tilt:	0° to 18°
Security	Kensington Security Slot:	Yes
Dimensions	Product with Base (W x H x D):	562.4 x 392.8 x 196.0 mm (22.1" x 15.4" x 7.7")
	Product w/o Base (W x H x D):	562.4 x 352.6 x 56.2 mm (22.1" x 13.9" x 2.2")
	Packaging (W x H x D):	672.0 x 517.0 x 249.0 mm (26.5" x 20.4" x 9.8")
Weight	Product w/o Base:	7.3 kg(16.1 lb)
	Product with Base:	8.1kg(17.9lb)
	Packaging:	11.2kg(24.7lb)
Regulation Approval	Certifications & Compliance:	CB, CE, FCC, RoHS, WEEE, REACH
Accessories	Supplied:	Power Adaptor, Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card
Optional Accessories	Ceiling Mount (Landscape only):	CMP-01+WMK-03
	Wall Mount (Landscape only):	WMA-01, WMK-01, WMK-03, PMK-01
	Desk mount (Landscape only):	DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02
Power	Power Supply:	External
Storage Conditions	Temperature:	-20°C-60°C (-4°F-140°F)
	Humidity:	5%-95% (non-condensing)