

## WyreStorm CAM-0402-BRG 4K30Hz Camera Bridge / 4 Wired Inputs 2 HDMI 2 USB / HDMI USB Output / Multiview / RS232

Inputs	2 x USB 3.0 Type-A up to 3840x2160@30Hz MJPEG, 2 x HDMI up to 3840x2160@30Hz
Outputs	1 x USB Type-C up to 3840x2160@30Hz MJPEG, 1 x HDMI up to 3840x2160@30Hz
Multiview Support	HDMI out and USB HOST share same signal up to quad-view
Control Options	RS-232, Web GUI, LAN
OS Compatibility	Windows 10 or above, macOS 10.15 or above
USB Protocols	UVC, UAC
HDCP Compliance	HDCP 2.2
CEC Support	HDMI outputs support CEC one-touch play and standby
EDID Configuration	Web UI, API adjustable, Default 4K@30Hz stereo audio
Video Formats	HDMI up to 4K@30Hz, USB MJPEG up to 4K@30Hz
Audio Formats - HDMI IN	RAW PCM 16-bit 2-channel 32/44.1/48KHz
Audio Formats - USB IN	RAW PCM 16-bit 2-channel 16/32/48KHz
Audio Formats - HDMI OUT	RAW PCM 16-bit 2-channel 48KHz
Audio Formats - USB HOST	RAW PCM 16-bit 2-channel 48KHz
Supported Standards	DCI, RGB
Maximum Pixel Clock (HDMI)	300MHz
Power Supply	DC 20V/3A 5.5/2.1mm barrel
Power Consumption	36W
Supported Resolution	3840x2160@30Hz
Mirrored Multiview	USB HOST and HDMI OUT support mirrored multiview output
Firmware Updates	Web-based firmware upgrade
Audio Support	Audio over HDMI and USB PCM 2-channel
Indicators	Power indicator, OLED screen