

Kramer C-5BM/5BM-50 50ft 5 BNC RGBHV Mini Coax Cable

Coax Center Conductor:	28 AWG 7/36 tinned copper.
Dielectric:	Foam polyethylene.
Shield:	90% braid 38 AWG tinned copper.
Coax Jacket Colors:	Red, green, blue, yellow, black.
Outer Jacket:	PVC.
Outer Jacket Color:	Dark gray with white lettering.
DIAMETERS	
Center Conductor:	0.38mm (0.015in).
Individual Coax:	2.75mm (0.108in).
Outside Diameter:	9.2mm (0.362in).
ELECTRICAL	
Impedance:	75ohm.
DC Resistance:	237ohm/km (72.2ohm/1000ft).
Capacitance:	60pF/m (18.3pF/ft).
Velocity of Propagation:	78%.
Temperature:	-20° to +75°C (-4° to +167°F).
Attenuation (dB/100 ft.):	-0.6dB @1MHz -1.4dB @5MHz -2.1dB @10MHz -4.7dB @50MHz -6.8dB @100MHz -9.2dB @180MHz -14.2dB @400MHz -20.1dB @750MHz -23.8dB @1000MHz.
REGULATORY	
UL:	CL2.
CSA:	C(UL) CL2.
Dielectric:	1.6mm (0.063in).