

**Datavideo TLM-170KR 17.3in 4K UHD ScopeView Rackmount Monitor / 12G-SDI / HDMI 2.0 / HDR**

Screen	17.3" LED Backlit
Chassis	Rack Mount
Resolution	3840x2160
Viewing Angle (H)	+89/-89deg
Viewing Angle (V)	+89/-89deg
Luminance/Contrast	300cd/m2 1000:1
Video Inputs	1 x 12G SDI2 x HDMI (2.0)
Loop Through	1 x 12G SDI1 x HDMI (2.0)
Supported Input Resolutions (SDI)	4096x2160p (23.98/24/25/29.97/30/50/59.94/60), 3840x2160p (23.98/24/25/29.97/30/50/59.94/60), 4096x2160Psf (23.98/24/25/29.97/30), 3840x2160Psf (23.98/24/25/29.97/30), 1920x1080p (23.98/24/25/29.97/30/50/59.94/60), 1920x1080i (50/59.94/60), 1920x1080Psf (23.98/24/25/29.97/30), 1280x720p (23.98/24/25/29.97/30/50/59.94/60), 525i, 625i
Supported Input Resolutions (HDMI)	4096x2160p (23.98/24/25/29.97/30/50/59.94/60), 3840x2160p (23.98/24/25/29.97/30/50/59.94/60), 1920x1080p (23.98/24/25/29.97/30/50/59.94/60), 1920x1080i (50/59.94/60), 1280x720p (23.98/24/25/29.97/30/50/59.94/60), 720x480i (NTSC), 720x576i (PAL), 640x800, 800x600, 1024x768, 1280x800
Aspect Ratio	16:9, 4:3
Aspect Marker	YES
Safty Marker	YES
Tally LED	Live (Red), Cued (Green)
Audio In/Out	Input: Embedded Audio (48KHz sampling), Output: Analog stereo (Phone Jack), Speaker x 2 (3W)
Special Features	waveform, vector scope, Focus Peaking, False Color, Exposure (Zebras), Histogram, HDR / SDR, Time Code, Audio Vector, Camera Log,Gamma, Marker, Pixel to Pixel, Zoom, H/V Delay, DSLR, Freeze, Image Flip, Check Field, Level Meter, Color Bar, Color Calibration
Dimension (WxHxD)	403 x 305 x 37 mm
Weight	5.2kg
Operating Temp. Range	0~40 deg C
Power	DC 12V, 40.1W
What's in the Box	1 x TLM-170KR product 1 x AD Switch DC 12V 2 x Rack kit 8 x Screw phi 3.0*6m/m 8 x Screw M5 x 10mm 5 x Cable tie