

Luxul XAP-1610 Wave 2 AC3100 Dual-Band Access Point PoE+ / MU-MIMO / Beamforming

High performance 802.11ac WiFi	data transfers up to 3167Mbps
Concurrent Dual-Band Wireless AC	2.4 GHz / 5 GHz
2.4 and 5GHz Beamforming	yes
High output power for maximum coverage	1000mW, 30dBm
Compatible with Luxul Roam Assist Wireless Controllers	Roam Assist compatible
VLAN support for creating a secure guest network	802.1Q
Simple and discreet installation	ceiling/wall/desktop
Up to 4 SSIDs per band	8 SSIDs total
Single cable installation with PoE	PoE+ capable
Great for streaming media or other demanding applications	low-latency streaming
Installs on ceiling or wall; or use as a desktop AP	ceiling wall desktop
Three-year limited warranty	3 years
Supports 128 clients	128 clients
Wave 2 technology	MU-MIMO
Height	7.28 in (18.5 cm)
Length	7.28 in (18.5 cm)
Operating Temperature	32° to 122°F (0° to 50°C)
Product Weight	1.5 lbs (0.7 kg)
Shipping Dimensions	12.01" x 9.45" x 3.21" (305.1 x 240.1 x 81.6 mm)
Shipping Weight	3.35 lbs (1.5 kg)
Width	1.71 in (4.3 cm)
Access Point Location	Indoor
Antenna Type	4x4 MU-MIMO Wave 2
Beamforming	
Connection Type	Wireless
Power Cord	US Cord
Power Type	AC
PoE	
Special Features	Kits
SSID Capability	8
TAA Compliant	No
Transmit Power (Maximum)	1000mW, 30dBm

UPC	655003920970
VLAN Compliance	802.1Q
Wireless Frequencies	2.4 GHz, 5 GHz
Wireless Mode	802.11 a/b/g/n/ac
Certifications	FCC, IC, NDAA 889, RCM, RoHS