

Middle Atlantic RLNK-215 Select Series PDU with RackLink/2 Outlet/15A/IP Controled

| | | RLNK-215 |
|----------------------------------|--|--|
| SUMMARY | Form Factor | In-Line Module |
| | Max Load | 15A |
| | Rated Load | 12A |
| | Surge Protection | basic |
| | Sequencing | yes |
| | # of Outlets | 2 total / 2 controlled |
| | Integrated Web Server | yes |
| AC POWER | Connection Type | 2 ft. IEC(15A) |
| | Line Voltage | Nominal: 120VAC / Minimum: 80VAC / Maximum: 140VAC |
| | Maximum Peak Load | 15 Amps |
| | Maximum Cont.Load | 12 Amps |
| | No Load Power Dissipation | Less Than 1W Note: Ethernet disconnected, all relays off |
| BASIC SURGE SPECIFICATION | Peak Impulse Current (8/20uS Waveform) | 12,000 Amps, one time, 9,000 Amps, two times within 5 minutes - Maximum peak impulse current pulse as defined between line and neutral - Maximum multiple impulse current derated per spec |
| | Protection Mode | Line to Neutral only; no ground contamination |
| | Response Time | Less than 1 nanosecond |
| | Surge Energy Dissipation | 120 Joules (10/100 micro seconds) |
| | EMI/RF Supression | >20dB Calculated Line to Neutral -100kHz to 1 Mhz - based on nominal impedance |
| REGULATORY APPROVALS | Safety | UL 60950-1 and CSA C22.2 No. 60950-1 |
| | EMI/RF | FCC Part 15, Class B |
| EVENT DRIVEN/ RESPONSES | AutoPing No Response/Recovery | Email and/or Control Outlet |
| GENERAL | Operating Temperature Range | 32-104°F(0-40°C) |
| | Humidity Range | 0-95% RH, non-condensing |
| | Communication | SSL/TLS, SMTP, NTP, DDNS, Cloud, TCP/IP, HTTP (integrated web server) |
| | Warranty | 3 years limited warranty |