

Apantac OG-DL-4+4 OG-DL-4+4 openGear-Based Multiviewer

Category	Specification
Inputs	4 x BNC (3G-SDI / HD-SDI / SD-SDI) Female
	4 x HDMI Female
	Embedded Audio: HDMI
	Outputs: 1x HDMI Female
	Outputs: 1x BNC (3G-SDI) Female
Interfaces	4 x BNC (3G-SDI / HD-SDI / SD-SDI) Female
	4 x HDMI Female
	Embedded Audio: HDMI
	Outputs: 1x HDMI Female
	Outputs: 1x BNC (3G-SDI) Female
	Other I/O: 1x BNC (Timecode) Input; 1x RJ45 (GPI) Input/Output
Standards	HDR Support: No
	HDCP Support: No
	EDID Support: No
	Audio Decoding: No
Transmission	Video Format: HDMI
	1920 x 1080p @ 60/50 fps
	Video Format: SDI
	1920 x 1080p @ 60/50 fps
	PC Resolutions: 1600 x 1200 @ 50/60 Hz; 1920 x 1200 @ 50/60 Hz
Power	Power I/O: 1x IEC C14 Input
	Power Consumption: 90 to 250 VAC (550 W)
General	Rack Form Factor: 2 RU
	Dimensions: 23.6 x 17.6" / 600.0 x 446.0 mm