

AJA U-TAP-HDMI Simple USB 3.0 Powered HDMI Capture

Video Formats

- Video
 - (HD) 1920 x 1080p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
 - (HD) 1920 x 1080i 25, 29.97, 30
 - (HD) 1280 x 720p 50, 59.94, 60
 - (SD) 625i 25
 - (SD) 525i 29.97
- Computer
 - 1920 x 1200p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
 - 1680 x 1050p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
 - 1600 x 1200p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
 - 1280 x 1024p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
 - 1280 x 960p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
 - 1024 x 768p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
 - 800 x 600p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
 - 720 x 576p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
 - 640 x 480p 23.98, 24, 25, 29.97, 30, 50, 59.94, 60
- Scaled
 - 1920 x 1200p 25, 29.97, 30, 50, 59.94, 60
 - 1920 x 1080p 25, 29.97, 30, 50, 59.94, 60
 - 1280 x 720p 25, 29.97, 30, 50, 59.94, 60
 - 1024 x 576p 25, 29.97, 30, 50, 59.94, 60
 - 856 x 480p 25, 29.97, 30, 50, 59.94, 60
 - 768 x 576p 25, 29.97, 30, 50, 59.94, 60
 - 720 x 576p 25, 29.97, 30, 50, 59.94, 60
 - 720 x 480p 25, 29.97, 30, 50, 59.94, 60
 - 640 x 480p 25, 29.97, 30, 50, 59.94, 60
 - 640 x 360p 25, 29.97, 30, 50, 59.94, 60

Video Input Digital

HDMI v1.4a, 24-bits/pixel, RGB or YUV

Audio Input Digital

2-Channel, 24-bit HDMI embedded audio, 48 kHz sample rate

Host Interface

USB 3.0/USB 2.0 UVC/UAC compliant

Size (w x d x h)

3.3" x 2.4" x 1.0" (84mm x 61mm x 25mm)

Weight

0.3 lb (0.2 kg)

Power

5V USB bus powered; 6.5W max

Environment

- Safe Operating Temperature: 0 to 40 degrees C (32 to 104 degrees F)
- Safe Storage Temperature (Power OFF): -40 to 60 degrees C (-40 to 140 degrees F)
- Operating Relative Humidity: 10-90% noncondensing
- Operating Altitude: <3,000 meters (<10,000 feet)