

# Adder ALDV120R AdderLink AV Digital DVI Extender (Receiver)

## Approvals / Compliance

- CE
- FCC

## Standards

DVI-D interface: The system supports resolutions such as 480p, 720p, 1080p or WUXGA (1920 x 1200) @ 60Hz (with reduced blanking) and 24bit color depth.

Hardware compatibility: All computers with DVI-D and USB connections

## Cable Guidelines

Important extension distance information

- Recommended cables are CAT7 shielded foiled twisted pairs: Daetwyler 7702 Flexible patch cable Daetwyler 7120 Bulk cable
- CAT6 (or better) shielded twisted pair cable must be used to connect the local and remote units in order to maintain compliance with radio frequency energy emission regulations and ensure a suitably high level of immunity to electromagnetic disturbances
- Note: Distances are achieved using single lengths of trunk/bulk cable. For each break/patch connection reduce distance by 5m (16ft). Preferably patch cables should be of type CAT7 and less than 2m (6.5ft). Patch cables over 2m (6.5ft) must be CAT7.

Resolution	Frequency	Patch Connections	Cable Type	Distance
1920x1200	60Hz	0	CAT7	50 metres
1920x1200	60Hz	0	CAT6a (shielded)	50 metres
1920x1200	60Hz	2	CAT6a (shielded)	40 metres
1920x1200	60Hz	2	CAT7	40 metres

## Environmental

Operating Temperature: 0 to 40°C / 32 to 104°F

## Connectors - Local Unit

Computer connections at transmitter (TX) DVI-D male, USB type A (for power only)

## Connectors - Remote Unit

Display connections at receiver (RX) DVI-D male

## Mechanical

Injection molded ABS cases

45mm / 1.8" (w) x 63mm / 2.5"(d) x 21mm / 0.8"(h) with 30cm / 12" pigtails

Weight 250g / 0.6 lb per pair

## Power

USB powered, 5VDC -2.5W for both RX and TX units combined

## Software

Compatible with all known operating systems