

Kramer VGAA-IN8-F64 8-Channel VGA with Analog Audio Input Card

PORTS

- 8 VGA on 15-pin HD connectors, 8 unbalanced analog audio on 3.5mm mini jack connectors (accessible via C GF/GMAF-30 cables)

BANDWIDTH

- 450MHz

MAXIMUM RANGE

- 10m (32ft)

POWER CONSUMPTION

- 35W

OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

HUMIDITY

- 10% to 90%, RHL non-condensing

SAFETY REGULATORY COMPLIANCE

- CE

ENVIRONMENTAL REGULATORY COMPLIANCE

- Complies with appropriate requirements of RoHs and WEEE

INCLUDED ACCESSORIES

- 8 C-GF/GMAF-30 cables

PRODUCT DIMENSION

- 39.50cm x 18.00cm x 2.00cm (15.55" x 7.09" x 0.79") W, D, H

PRODUCT WEIGHT

- 0.7kg (1.4lbs) approx

SHIPPING DIMENSION

- 19.00cm x 12.50cm x 5.80cm (7.48" x 4.92" x 2.28") W, D, H

SHIPPING WEIGHT

- 0.8kg (1.8lbs) approx