

Kramer VM-2D 1x2 4K60 4x2x0 DVI Distribution Amplifier

INPUTS

- 1 DVI: On a DVI-I female connector

OUTPUTS

- 2 DVI: On DVI-I female connectors

VIDEO

- Max. Data Rate: 10.2Gbps (3.4Gbps per graphic channel)
- Max. Resolution: 4K@60Hz (4:2:0) 24bpp
- Standards Compliance: DVI 1.0, HDMI 2.0 and HDCP 1.4

USER INTERFACE

- Controls: EDID setup button, RS-232 port on mini-USB female connector for firmware upgrade
- Indication LEDs: OUTPUTS 1 to 2, ACTIVE input and power ON LEDs

POWER

- Source: 5V DC, 4A
- Consumption: 5V DC, 800mA

ENCLOSURE

- Size: Tools
- Type: Aluminium
- Cooling: Convection ventilation

ENVIRONMENTAL CONDITIONS

- Operating Temperature: 0° to +40°C (32° to 104°F)
- Storage Temperature: -40° to +70°C (-40° to 158°F)
- Humidity: 10% to 90%, RHL non-condensing

ACCESSORIES

- Included: Power supply, bracket set
- Optional: RK-3T 19" rack adapter

PRODUCT DIMENSION

- 12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

PRODUCT WEIGHT

- 0.3kg (0.6lbs) approx

SHIPPING DIMENSION

- 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

SHIPPING WEIGHT

- 0.7kg (1.5lbs) approx