

A-NeuVideo ANI-03TCDRX Optical Audio 492 feet (150M) over Single CAT5e/6/7 Extender (Receiver)

- **Input Port:** Optical
- **Output Port:** Optical
- **Control Port:** RS-232
- **Audio Sampling Rate:** Up to 192kHz
- **Audio Format:** LPCM 2CH, Dolby Digital 2~5.1CH and DTS 2~5.1CH (Pass through)
- **CAT Cable Distance:**
 - 192k@328ft/100M
 - 96k@492ft/150M
 - 48k@984ft/300M
- **Power Supply:** 12V / 1.25A DC (US/EU standards, CE/FCC/UL certified)
- **ESD Protection Human Body Model:**
 - ± 8kV (air-gap discharge)
 - ± 6kV (contact discharge)
- **Dimensions (WxDxH):** 3 x 3.3 x 1.2 in (78.5x83.5x30mm) w/ Connector / 3 x 2.8 x 1.2 in (78.5x72x30mm) w/o Connector
- **Chassis Material:** Metal
- **Silkscreen Color:** Black
- **Operating Temperature:** 0°C~40°C / 32°F~104°F
- **Storage Temperature:** -20°C~60°C / -4°F~140°F
- **Relative Humidity:** 20 ~ 90% RH (non-condensing)
- **Power Consumption:** 0.85W