

PreSonus Sceptre S8 8 inch Coaxial Near Field Studio Monitor with DSP Processing

Inputs	
1- Balanced XLR	
1- Balanced ¼" TRS	
Frequency Response (-3 dB)	46 Hz - 20 kHz
Frequency Response (-10 dB)	38 Hz - 23 kHz
Crossover Frequency	2.4 kHz
LF Amplifier Power (@ 4Ω)	90W
HF Amplifier Power (@ 4Ω)	90W
Peak SPL (@ 1 meter)	116 dB
LF Driver	8" glass-reinforced paper
HF Driver	1" diaphragm compression driver
Input Impedance	10 kΩ
User Controls	
Volume Range	A-type taper
HF Control	Flat, +1, -1.5, -4 dB
Low Cut	Flat, 60, 80 Hz, 100 Hz
Acoustic Space	Flat, -1.5, -3, -6 dB
Protection	
RF interference	
Over-current	
Over-voltage	
Over-temperature	
Turn-on/off transient	
Subsonic filter	
External mains fuse	
Power	
100-120V ~50/60 Hz or 220-240V ~50/60 Hz	
Cabinet	
Vinyl-laminated, medium-density fiberboard	
Physical	
Width	11.4" (290 mm)
Depth	13.3" (338 mm)
Height	15.75" (400 mm)
Weight	24.25 lbs (11 kg)