

PreSonus Temblor T8 8 inch Active Subwoofer with Built In Crossover

Inputs	
2- Balanced ¼" TRS 2- Unbalanced RCA	
Outputs	
2- Balanced ¼" TRS (full range with 80 Hz HPF option) 2- Unbalanced RCA (full range with 80 Hz HPF option)	
Performance	
Frequency Response	30 Hz - 200 Hz
Low Pass Filter Frequency	50 - 130 Hz (variable)
Signal-to-Noise Ratio	>98 dB (A weighted)
THD	0.05%
Amplifier Power	200W peak, 100W RMS
Power Consumption	120W
Amplifier Type	Class AB
Peak SPL at 1m	104 dB
Woofer	8" glass-composite, downward-firing
Acoustic Port	Front-firing bass reflex (round)
User Controls	
Input Gain Range	-30 to +6 dB
Polarity Switch	0° or 180°
Low Pass Filter Control	50 Hz to 130 Hz
High Pass Filter Switch	On/Off
Protection	
RF interference Output-current limiting Over-temperature Turn-on/off transient Subsonic filter External mains fuse	
Power	
100-120V ~50/60 Hz or 220-240V ~50/60 Hz	
Cabinet	
Vinyl-laminated MDF	
Physical	
Width	10.2" (260 mm)
Depth	12.6" (320 mm)
Height	11" (280 mm)
Weight	21.2 lbs (9.6 kg)