

PreSonus AIR15 2-Way 15inch 1200W Active Loudspeaker

Acoustic Performance	
Configuration	Active 2-way
Frequency Range (-3 dB)	47 Hz to 20 kHz
Frequency Range (-10 dB)	40 Hz to 20 kHz
Crossover Frequency	1.6 kHz
Maximum Output	124 dB SPL
Nominal Dispersion (HxV)	90° x 60°
Transducer	
LF Driver	15" (2.5" voice coil)
HF Driver	1.35" compression
Amplifier	
Amplifier Type	Class D (LF), Class AB (HF)
Total System Power	1,200W dynamic
LF Power	900W
HF Power	300W
Connections and Controls	
Inputs	2 x XLR/TRS mic/line combo; 1 x 1/8" TRS stereo
Outputs	1 x XLR Mix Out
DSP	
DSP Features	LCD screen with EQ and multiple presets
Enclosure	
Cabinet	H-PP molded
Grille	1.2 mm steel
Handles	1 top, 1 side
Flypoints	2 top, 1 back
Pole Mounting	Dual position (0°, 7.5°)*
Dimensions (H x W x D)	30.6" x 16.9" x 15.8" (778 mm x 430 mm x 402 mm)
Weight	46.3 lbs (21 kg)
Power	
Power Input	115V / 230V ~50/60 switchable
Maximum Current	3.5A (230V-50 Hz), 7A (120V)