

Rockustics Periscope 4 4 inch 2-way Landscape speaker

Nominal Impedance	8 ohm
Impedance (min)	8 ohm
Sensitivity dB @ 2.83V/1M	93.0 dB
Sensitivity dB @ 1W/1M (2)	93.0 dB
Frequency Response (± 3 dB)	85 Hz - 22 kHz
Frequency Response (±10 dB)	50 Hz - 22 kHz
Max. Program Power	100 W
Max. Continuous Power RMS	50 W
Max. Power SPL @ 1 M	100.0 dB
Tap Selector	5 position integrated knob rotary switch with transformer bypass
70.7 Volt Transformer Taps	25W / 97.0 dB
100 Volt Transformer Taps (dB)	25W / 97.0 dB
Transformer Options	70.7 / 100 Volt option with 8 Ohm direct
Transducer - Low Frequency Driver	4" Polypropylene Cone with Butyl Rubber Surround
Transducer - High Frequency Driver	1" Convex Titanium Tweeter w/ Waveguide
Colors	Brown
Grille - material	Powder Coated Aluminum
Tweeter - part	1" Convex Titanium Tweeter w/ Waveguide
Inputs	Bare wire leads, positive and negative
Height (SM = Height)	450.9 mm / 17.75"
Diameter (SM = Width)	142.9 mm / 5.62"
Regulatory - CE	approved
Regulatory - RoHS	approved