

Rockustics Periscope 6 6 inch 2-way Landscape speaker

Nominal Impedance	8 Ohm
Impedance (min)	8 Ohm
Sensitivity dB @ 2.83V/1M	86.0 dB
Sensitivity dB @ 1W/1M (2)	86.0 dB
Frequency Response (± 3 dB)	60 Hz - 20 kHz
Frequency Response (± 10 dB)	55 Hz - 22 kHz
Max. Program Power	200W
Max. Continuous Power RMS	100W
Max. Power SPL @ 1 M	106.0 dB
Tap Selector	5 position integrated knob rotary switch with transformer bypass
70.7 Volt Transformer Taps	50W / 103.0 dB
100 Volt Transformer Taps (dB)	50W / 103.0dB
Transformer Options	70.7 / 100 Volt option with 8 Ohm direct
Transducer - Low Frequency Driver	6.5" Polypropylene Cone w/ Rubber Surround
Transducer - High Frequency Driver	1" Convex Titanium Tweeter w/ Waveguide
Colors	Brown
Grille - material	Powder Coated Alumnium
Tweeter - part	1" Convex Titanium Tweeter w/ Waveguide
Inputs	Bare wire leads, positive and negative
Height (SM = Height)	520.7 mm / 20.5"
Diameter (SM = Width)	219.1 mm / 8.62"
Regulatory - CE	approved
Regulatory - RoHS	approved