

ViewZ VZ-PVM-I3W3N 27 inch 1920x1080 IP Based Public View Monitor with 2MP Camera/White

DISPLAY	
Screen Size	27"
Max. Resolution	1920x1080 @60Hz
Pixel Pitch	0.31125 mm x 0.31125 mm
Brightness	300cd/m2(Typical)
Contrast Ratio	3000:1
Aspect Ratio	16:9
Viewing Angle (H/V)	178° /178°
Display Color	16.7 Million
Response Time	<12 ms
Video System	NTSC/PAL
Frequency(H)/Frequency(V)	30 ~ 84Khz / 50 ~ 75Hz
INTERFACE	
AV (Composite) In	1
Camera (CVBS) Out	1
HDMI In / VGA In (15Pin D-Sub)	1/1
Audio In/Out	1/1
Ethernet 10/100	1
DC12V Out (Camera Use)	1
SPECIAL FEATURES	
Multi Display Function	PIP/PBP
Filter Type	3D Comb-filter / De-Interlace
Analog Video Resolution (MAX)	600 TV Line
Multi-lingual Language	English, Spanish, French, Russian, Portuguese
AUDIO	
Built in Speaker	5Wx2
DIMENSIONS & WEIGHT	
Outline Dimension (W x H x D)	25.07" x 17.93" x 2.17"
	636.8mm x 455.60mm x 55.3mm
Net Weight /Gross Weight	28.66 lbs (13.00 kg) / 33.06 lbs (15.0 kg)
CAMERA	
Camera Type	2 Mega Pixel IP Camera
Image Sensor / Encoder Chipset	SONY IMX322 / Amba S233
Lens	DC Auto Iris 2.8~12mm Vari-focal Lens
Total / Effect Pixel	1920(H) x1080p(V) 30fps
Video Compression	H.264, MJPEG, CBR, VBR support
Video Out	1ch CVBS (NTSC/PAL) / 1ch RJ-45 output
Motion Detection	Support
Ethernet Port	10/100 Base-T
Web Application	IE 6" 11, Firefox
Network Protocol	TCP/IP, UDP, SMTP, HTTP, FTP, PPPOE DHCP, DNS, DDNS, UPNP, RTP, RTSP
Integration Protocol	ONVIF 2.4 (supported)
Function	2D/3D NR, D-ZOOM, DPC, HLC/BLC, Defog D/N, WDR, AGC, AWB
MEDIA CARC (Optional)	
External Storage	Support SD/SDHC CARD, USB 2.0 HOST
Output	VIDEO - HDMI(1080p) / AUDIO - L/R, HDMI
VIDEO Format	RM, RMVB, AVI, DVIX, MKV, MOV, HDMOV, MP4, M4V, PMP, AVC, FLV, VOB, MPG, DAT, MPEG, TS, TP, M2TS, WMV, H.264, H.263, WMV9, VC-1, MPEG1/2/4

VIDEO Resolution	1080P @60Hz
AUDIO Format	MPEG1/2/4, MP3, WMA, OGG, AAC, FLAC, APE, AC-3, DTS, ATRA, WAV, PCM
Image Format	JPEG, TIF, PNG, BMP
VIDEO Play Control	AUTO, REPEAT, ZOOM, RESUME, TIME
GENERAL	
Transmitter - IR Remote Control	YES
Power Electrical Ratings Consumption	AC 110~240V (50/60Hz) 24V DC / 3A < 46 W
Warranty Parts/ Labor MTBF (Approx.)	3 Year/3 Year 50,000 Hours
Operating Temperature	32-104°F/0-40°C
Regulation	cUL, FCC(A), CE
Compatible Mounts Wall Ceiling	VZ-WM50, VZ-AM02 VZ-CMKiT-01, VZ-CMKiT-02