

Kramer DIP-31 4K60 4x2x0 HDMI/Computer Graphics Automatic Video Switcher

INPUTS

- 2 HDMI on HDMI connectors, 1 VGA on a 15-pin HD (F) connector, 1 unbalanced stereo audio 1V RMS (nominal) on a 3.5mm mini jack

OUTPUTS

- 1 HDMI connector, 1 unbalanced stereo audio 1V RMS (nominal) on a 3.5mm mini jack

PORTS

- 1 Ethernet on an RJ-45 connector, 1 RS-232 3-pin terminal block control port, 1 RS-232 3-pin terminal block data port (internal use), 1 USB on mini USB connector

CONTROLS

- Remote switches for input switching, step-in, volume control, and device reset switch

STANDARDS

- HDMI with Deep Color, x.v.Color™ and 3D, HDCP—works with sources that support HDCP repeater mode

MAXIMUM ANALOG AUDIO LEVELS

- 3.1Vpp

SNR

- -70dBu

THD

- 0.013%

SUPPORTED WEB BROWSERS

- Windows 7 and higher: Internet Explorer (32/64 bit) version 11, Firefox version 30, Chrome version 35
- MAC:Chrome version 35, Firefox version 27, Safari version 7; Android OS: Chrome version 35; iOS:Chrome version 35, Safari version 7

POWER CONSUMPTION

- 12V DC, 600mA

OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

HUMIDITY

- 10% to 90%, RHL non-condensing

COOLING

- Convection

ENCLOSURE TYPE

- Aluminium

ENVIRONMENTAL REGULATORY COMPLIANCE

- Complies with appropriate requirements of RoHs and WEEE

INCLUDED ACCESSORIES

- Power supply, ADC-DPM/HF DisplayPort (M) to HDMI (F) adapter cable, (for connecting a DisplayPort source to the HDMI input), DIP-30BP black panel

OPTIONS

- Rack adapter RK-T2B

WARRANTY

- 7 years parts and labor

PRODUCT DIMENSION

- 18.75cm x 11.50cm x 2.54cm (7.38" x 4.53" x 1.00") W, D, H

PRODUCT WEIGHT

- 0.4kg (0.9lbs) approx

SHIPPING DIMENSION

- 34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H

SHIPPING WEIGHT

- 0.9kg (2.1lbs) approx