

Soundtube IPD-SM82-EZ-II-WH Dante enabled 8 inch Two-way Surface mount speaker (White)

System Type	Controlled
Frequency Response (- 3 dB)	50 Hz - 20 kHz Sealed: 70 Hz - 20 kHz
Frequency Response (- 10 aB)1	38 Hz - 20 kHz Sealed: 50 Hz - 20 kHz
Max. Power SPL91m?	101.0 dB
Coverage Angle (-6 dB @ 2 kHz)	70° Horizontal / 90° Vertical
Coverage Angle (-6 dB @ 10 kHz)	110° Horizontal / 100° vertical
Coverage Angle (averaged 2-10 kHz)	90° horizontal /105° vertical
Aiming Angle	0°-0Cr
Directivity Factor (Q)	5.20 (Averaged 100 Hz -10 kHz); 12.0 @ 2 kHz
Directivity Index (DI)	6.20 (Averaged 100 Hz -10 kHz); 10.8 @ 2 kHz
Transducer - Low-Frequency Driver	203.0 mm (8.0 in.) polypropylene woofer with butyl rubber
Transducer - High-Frequency Driver	25.0 mm (1.0 in) soft dome tweeter
Low-Frequency Voice Coil	38.1 mm (1.50 in) high temperature Kapton
Crossover Frequency	2.5 kHz
Network Type - Low Pass	12 dB per octave. 2nd order
Network Type-High Pass	12 dB per octave. 2nd order
Enclosure Material	High Impact Poly Styrene (HIPS)
Grille	Aluminum with powder-coat finish
Inputs	FU45 Ethernet Port
Colors	Black or white
Height	457.2 mm (18.00 in.)
Width	292.1 mm (11.50 in.)
Depth	251.0 mm {9.88 in.]
Weight	6.3 kg (13.9 lbs.)
CKinninn i Shipping Weight	7.0 kg (15.4 lbs.)
Included Accessories	Safety cable, wall mount bracket, port plug, allen wrench and watertight strain-relief bushing
Packaging	One per box
Regulatory - CE	Approved
Regulatory - UL	UL 60065 Listed
DECLJO nOrio	Approved
IP65 (sealed version)	Approved