

Kramer FC-21ETH 1-port Serial Control Gateway

PORTS

- 1 RS-232/RS-485 selectable on a 3-pin terminal block, 1 Ethernet on an RJ-45 connector, 1 mini USB connector for local services

SUPPORTED SERIAL PORT BAUD RATES

- 1200, 2400, 4800, 9600, 19200, 38400, 57600, 15200bps

RS-232 COMMUNICATION

- Transparent up to 115200bps

MAXIMUM DATA HANDLING OF DEVICE

- Up to 150kbps summed on all ports

CONTROLS

- Serial Select button, RS-485 terminator switch, DHCP and Factory Default buttons

INDICATORS

- Power, Ethernet, Serial 1, Serial I/O, and DHCP status LEDs

POWER CONSUMPTION

- 5V DC, 200mA

OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

HUMIDITY

- 10% to 90%, RHL non-condensing

COOLING

- Convection

ENCLOSURE TYPE

- Aluminum

INCLUDED ACCESSORIES

- Power adapter

VIBRATION

- ISTA 1A in carton (International Safe Transit Association)

SAFETY REGULATORY COMPLIANCE

- CE

ENVIRONMENTAL REGULATORY COMPLIANCE

- Complies with appropriate requirements of RoHs and WEEE

OPTIONS

- 19" rack adapter RK-3T

PRODUCT DIMENSION

- 21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72") W, D, H

PRODUCT WEIGHT

- 0.0kg (0.0lbs) approx

SHIPPING DIMENSION

- 35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83") W, D, H