

Kramer FC-69 HDMI Audio Embedder/De-Embedder

INPUT:	1 HDMI on an HDMI connector, 1 analog stereo audio on a 3.5mm mini jack.
OUTPUTS:	1 HDMI on an HDMI connector, 1 S/PDIF digital audio on an RCA connector, 1 analog stereo audio on a 3.5 mm mini jack.
OPERATION FREQUENCY:	Supports up to 8.91Gbps (2.97Gbps per graphic channel), 1080p @60Hz, 36-bit Deep Color.
COMPLIANCE WITH HDMI STANDARD:	Supports HDMI, HDCP.
CONTROLS:	8-way DIP-switch.
INDICATOR LEDS:	ON, IN, OUT, HDCP.
POWER SOURCE:	5V DC, 730mA.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
COOLING:	Convection.
ENCLOSURE TYPE:	Aluminium.
SHIPPING DIMENSIONS:	23.20cm x 12.00cm x 8.90cm (9.13" x 4.72" x 3.50") W, D, H
SHIPPING WEIGHT:	0.6kg (1.2lbs) approx.
RACK MOUNT:	With optional adapter.
FURNITURE MOUNT:	With included rubber feet.
PRODUCT WEIGHT:	0.4kg (0.88lbs) approx.
VIBRATION:	ISTA 1A in carton (International Safe Transit Association).
REGULATORY COMPLIANCE:	CE.
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE.
INCLUDED ACCESSORIES:	Power supply.
OPTIONS:	RK-3T 19" rack adapter.
WARRANTY:	7 years parts and labor.