

## Atlona AT-HDVS-CAM-W PTZ Camera for HDVS-300 Soft Codec Conferencing System/White

<b>Video</b>		
HD/SD/VESA (all resolutions are @30/25/20/15/10/5Hz)	1080p, 720p, 1680x896, 1024x768, 1024x576, 960x540, 800x600, 640x360, 720x576, 640x480, 352x288, 320x240, 320x180, 176x144	
Optical Zoom	10X, f = 4.7 ~ 47 mm	
Viewing Angle	6.43° (telephoto), 60.9° (wide-angle)	
AV	F1.6 - F3.0	
Minimum Illumination	0.5 lm, F1.8 with Automatic Gain Control ON	
Video Compression	H.264, H.265	
Control Protocol	VISCA/Pelco-D/Pelco-P	
Network Protocol	RTSP/RTMP, ONVIF	
Pan Rotation	±170°	
Tilt Rotation	-30° ~ ±90°	
Pan Control Speed	0.1 - 180° / sec	
Tilt Control Speed	0.1 - 80° / sec	
<b>Temperature</b>		
	Fahrenheit	Celsius
Operating	14 to 122	-10 to 50
Storage	-14 to 140	-10 to 60
Operating Humidity (RH)	20% to 95%, non-condensing	
Storage Humidity (RH)	20% to 80%, non-condensing	
<b>Power</b>		
Consumption	12 W	
Supply	Input: 110 - 220 V AC, 50/60 Hz Output: 12 V DC, 1 A	
<b>Dimensions</b>		
	Inches	Millimeters
H x W x D	6.59 x 5.90 x 5.90	167.5 x 150 x 150
<b>Weight</b>		
	Pounds	Kilograms
Device	3.08	1.4
<b>Certification</b>		
Device - CE, FCC		