

Kramer GALIL 4-C(W) 4 inch 2 Way Closed Back Ceiling Speakers

DESCRIPTION:	2-way closed-back ceiling speakers.
FREQUENCY RESPONSE:	85Hz to 20kHz @-10dB, 100Hz to 20kHz @±3dB.
WOOFER:	4" (103mm) polypropylene with rubber surround.
TWEETER:	0.5" (13mm) Mylar.
IMPEDANCE:	8? (transformer tap in off position).
TRANSFORMER TAPS:	70V – 30W/15W/7.5W/3.7W/Off (Lo-Z), 100V – 30W/15W/7.5W/Off (Lo-Z).
SENSITIVITY:	85dB SPL, 1W@1m.
MAX SPL:	Continuous: 95dB, peak: 97dB.
POWER HANDLING:	30W RMS, 80W continuous program.
CROSSOVER FREQUENCY:	6kHz.
COVERAGE ANGLE:	90°.
DIRECTIVITY FACTOR (Q):	4.2 averaged 1kHz to 10kHz.
DIRECTIVITY INDEX (DI):	6.2dB averaged 1kHz to 10kHz.
INPUT CONNECTOR:	Terminal block.
MATERIALS:	ABS bezel, aluminum grill, metal back can.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
WEIGHT PER SINGLE SPEAKER:	1.75kg (3.9lbs) approx.
SHIPPING WEIGHT (FOR PAIR):	6.1kg (13.5lbs) approx.
DIMENSIONS:	External diameter: 19.5cm (7.68"); cutout diameter: 16.7cm (6.57").
INSTALLATION CLEARANCE:	Mounting depth: 10.7cm (4.2").
ACCESSORIES:	Installation bracket, safety cord attached to grill, ceiling mounting kit, cutout template.
COLOR:	White.