

Kramer GALIL 4-O(W) 4 inch On-Wall 2-Way Speakers - White

DESCRIPTION:	2-way on-wall speakers.
FREQUENCY RESPONSE:	90Hz to 20kHz @-10dB, 160Hz to 16kHz @±3dB.
WOOFER:	4" (101.5mm) polypropylene cone.
TWEETER:	0.5" (13mm) Mylar.
IMPEDANCE:	8? (transformer tap in off position).
TRANSFORMER TAPS:	70V - 5W/2.5W/1.2W/Off (Lo-Z), 100V - 10W/5W/2.5W/Off (Lo-Z).
SENSITIVITY:	89dB 1W @1m.
MAX SPL:	Continuous:95dB, peak: 98dB.
POWER HANDLING:	20W RMS, 60W continuous program.
CROSSOVER FREQUENCY:	6kHz.
DIRECTIVITY FACTOR (Q):	4 averaged 1kHz to 10kHz.
DIRECTIVITY INDEX (DI):	6dB averaged 1kHz to 10kHz.
INPUT CONNECTORS:	Terminal blocks.
MATERIALS:	Frame, grill and brackets steel; cabinet ABS.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
WEIGHT PER SINGLE SPEAKER:	1.2kg (2.65lbs) approx.
WEIGHT WITH MOUNTING KIT:	1.6kg (3.5lbs) approx.
SHIPPING WEIGHT (FOR PAIR):	3.2kg (7.05lbs) approx.
DIMENSIONS:	11.9cm x 10.5cm x 18.8cm (4.7" x 4.13" x 7.4"), W, D, H.
DIMENSIONS WITH MOUNTING BRACKETS:	18.5cm x 10.7cm x 20.9cm (7.28" x 4.23" x 8.2"), W, D, H.
INSTALLATION CLEARANCE:	Front panel to wall (with mounting bracket): 15cm (5.9"), back panel to wall (with mounting bracket): 4.5cm (1.8").
ACCESSORIES:	2 mounting brackets (including 4 knobs and 4 mounting screws).
OPTIONS:	BCP-2S speaker cable.
COLORS:	Available in white or black.