

Kramer GALIL 5-O(W) 5.25 inch 2-Way On-Wall Speakers

DESCRIPTION:	2-way on-wall speakers.
FREQUENCY RESPONSE:	80Hz to 20kHz @-10dB, 100Hz to 20kHz @±3dB.
WOOFER:	5.25" (133mm) polypropylene cone.
TWEETER:	0.5" (13mm) Mylar.
IMPEDANCE:	8? (transformer tap in off position).
TRANSFORMER TAPS:	70V – 20W/10W/5W/2.5W/Off (Lo-Z), 100V – 20W/10W/5W/Off (Lo-Z).
SENSITIVITY:	89dB 1W @1m.
MAX SPL:	Continuous: 103dB, peak: 106dB.
POWER HANDLING:	30W RMS, 80W continuous program.
CROSSOVER FREQUENCY:	7.2kHz.
DIRECTIVITY FACTOR (Q):	4.0, averaged 1kHz to 10kHz.
DIRECTIVITY INDEX (DI):	6.0 dB averaged 1kHz to 10kHz.
INPUT CONNECTORS:	Terminal blocks.
MATERIALS:	Frame, grill and brackets steel; cabinet ABS.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
WEIGHT PER SINGLE SPEAKER:	2kg (4.4lbs) approx.
WEIGHT WITH MOUNTING KIT:	2.4kg (5.3lbs) approx.
SHIPPING WEIGHT (FOR PAIR):	4.8kg (10.6lbs) approx.
DIMENSIONS:	18.5cm x 16.5cm x 24.9cm (7.28" x 6.5" x 9.8"), W, D, H.
DIMENSIONS WITH MOUNTING BRACKETS:	18.5cm x 16.7cm x 27cm (7.28" x 6.6" x 10.6"), W, D, H.
INSTALLATION CLEARANCE:	Front panel to wall (with mounting bracket): 21cm (8.2"), back panel to wall (with mounting bracket): 4.5cm (1.8").
ACCESSORIES:	2 mounting brackets (including 4 knobs and 4 mounting screws).
OPTIONS:	BCP-2S speaker cable.
COLOR:	Available in white.