

Kramer GALIL 6-C(W) 6.5 inch 2-Way Closed-Back Ceiling Speakers

DESCRIPTION:	2-way closed-back ceiling speakers.
FREQUENCY RESPONSE:	80Hz to 20kHz @ -10dB, 95Hz to 20kHz @ ± 3 dB.
WOOFER:	6.5" (165mm) polypropylene with rubber surround.
TWEETER:	0.5" (13mm) Mylar dome.
IMPEDANCE:	8 Ω (transformer tap in off position).
TRANSFORMER TAPS:	70V - 3.7W/7.5W/15W/30W/Off (Lo-Z), 100V - 7.5W/15W/30W/Off (Lo-Z).
SENSITIVITY:	87dB SPL, 1W @1m.
MAX SPL:	Continuous: 100.7dB, peak: 103.7dB.
POWER HANDLING:	30W RMS, 80W continuous program.
CROSSOVER FREQUENCY:	9.2kHz.
COVERAGE ANGLE:	101 $^{\circ}$.
DIRECTIVITY FACTOR (Q):	7.5 averaged 1kHz to 10kHz.
DIRECTIVITY INDEX (DI):	8.6dB averaged 1kHz to 10kHz.
INPUT CONNECTOR:	Terminal block.
MATERIALS:	ABS bezel, aluminum grill, metal back can.
OPERATING TEMPERATURE:	0 $^{\circ}$ to +40 $^{\circ}$ C (32 $^{\circ}$ to 104 $^{\circ}$ F).
STORAGE TEMPERATURE:	-40 $^{\circ}$ to +70 $^{\circ}$ C (-40 $^{\circ}$ to 158 $^{\circ}$ F) .
HUMIDITY:	10% to 90%, RHL non-condensing.
WEIGHT PER SINGLE SPEAKER:	2.85kg (6.28lbs) approx.
SHIPPING WEIGHT (FOR PAIR):	8kg (17.64lbs) approx.
DIMENSIONS:	External diameter: 25.1cm (9.88"); cutout diameter: 22.4cm (8.82").
INSTALLATION CLEARANCE:	Mounting depth: 19.6cm (7.72").
ACCESSORIES:	Installation bracket, safety cord attached to grill, ceiling mounting kit, cutout template.
COLORS:	Available in white.