

Kramer GALIL 6-O(B) 6.5 inch 2-Way On-Wall Speakers - Black

DESCRIPTION:	2-way on-wall speakers.
FREQUENCY RESPONSE:	65Hz to 20kHz @-10dB, 80Hz to 20kHz @±3dB.
WOOFER:	6.5" (165mm) polypropylene cone with rubber surround.
TWEETER:	1" (25mm) silk dome.
IMPEDANCE:	8? (transformer tap in off position).
TRANSFORMER TAPS:	70V - 30W/15W/7.5W/3.7W/Off (Lo-Z), 100V - 30W/15W/7.5W/Off (Lo-Z).
SENSITIVITY:	87dB SPL, 1W @1m.
MAX SPL:	Continuous: 102dB, peak: 105dB.
POWER HANDLING:	40W RMS, 110W continuous program.
CROSSOVER FREQUENCY:	4.3kHz.
DIRECTIVITY FACTOR (Q):	3.9 averaged 1kHz to 10kHz.
DIRECTIVITY INDEX (DI):	5.9dB averaged 1kHz to 10kHz.
INPUT CONNECTORS:	Terminal blocks.
MATERIALS:	Frame, aluminum grill, steel brackets and ABS cabinet.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
WEIGHT PER SINGLE SPEAKER:	2.8kg (6.2lbs) approx.
WEIGHT WITH MOUNTING KIT:	3kg (6.6lbs) approx.
SHIPPING WEIGHT (FOR PAIR):	6.6kg (14.6lbs) approx.
DIMENSIONS:	21.5cm x 19.4cm x 30.1cm (8.5" x 7.6" x 11.9"), W, D, H.
DIMENSIONS WITH MOUNTING BRACKETS:	21.5cm x 22.5cm x 30.1cm (8.5" x 8.9" x 11.9"), W, D, H.
INSTALLATION CLEARANCE:	Front panel to wall (with mounting bracket): 22.7cm (8.9"), back panel to wall (with mounting bracket): 3.8cm (1.5").
ACCESSORIES:	2 mounting brackets (including 4 knobs and 4 mounting screws).
OPTIONS:	BCP-2S speaker cable.
COLORS:	Available in white or black.