



VS-6464DN DVI/HDCP I/O Card Installation Sheet

The **VS-6464DN** I/O Card mounts in one of the 16 slots on the rear of the **VS-6464DN** chassis. Slots are numbered from left to right and must be filled consecutively from left to right, **without leaving empty slots**.

WARNING: An input card must be mounted only in a slot designated for input cards (slots 1 to 4 and 9 to 12) and an output card must be mounted only in a slot designated for output cards (slots 5 to 8 and 13 to 16).

To install an I/O card:

1. Power off the **VS-6464DN** and all devices connected to it.
2. Using a Phillips screwdriver, loosen the screws at the top and bottom of the blanking plate.
3. Remove the blanking plate from the slot and store it for possible future use.



4. Remove the new card from its shipping box and anti-ESD bag.
5. Holding the card by the upper and lower handle, align the card with the plastic guide rails.
6. Slide the card into the chassis until the front of the card makes contact with the connector inside the chassis.
7. Press the card firmly into the slot until the connector plate is flush with the rear panel of the chassis and the connector is fully seated.
8. Using a Phillips screwdriver, tighten the retaining screws at the top and bottom of the card to secure it to the chassis.
9. Power on the **VS-6464DN** and follow the procedure in the **VS-6464DN** User Manual (see Section 9) to configure the new card.
10. Power on the peripheral devices.



Kramer Electronics Ltd.



P/N: 2900-300233



Rev: 1

VS-6464DN DVI/HDCP
I/O Card Installation Sheet
(P/N: 2900-300233 REV 1)