

Kramer KDS-DEC3 H.264 signals up to 1080p60 Decoder

OUTPUTS:	1 HDMI, 1 unbalanced stereo audio on a 3.5mm mini jack.
PORTS:	2 Ethernet on RJ-45 connectors (fully switched), 1 RS-232 on a 9-pin D-sub connector.
VIDEO SINGLE CHANNEL HD:	Up to 1920x1080p60 and 1920x1200(60Hz).
COMPRESSION STANDARD:	H.264/Mpeg4 Part 10 (AVC).
PROFILES:	Baseline, Main, High.
LEVELS:	Up to 4.2.
BIT RATES:	100Kbps to 25Mbps.
RATE CONTROL:	CBR, VBR, adjustable GOP (Group Of Pictures) size.
AUDIO COMPRESSION STANDARD:	MPEG4 AAC-LC.
CHANNELS:	2 channel (stereo), HDMI with digital L-PCM audio.
ANALOG SAMPLE FREQUENCY:	32, 44.1, and 48kHz.
BIT RATES:	96, 128, 192, and 256Kbps.
OUTPUT RESOLUTIONS:	1280 × 960, 1280 × 768, 1280 × 720, 1024 × 768, 852 × 480, 848 × 480, 800 × 600, 720 × 576, 720 × 480, 640 × 480, 1600 × 900, 1440 × 900, 1400 × 1050, 1366 × 768, 1360 × 768, 1280 × 1024, 1280 × 960, 1280 × 768, 1280 × 720, 1024 × 768, 852 × 480, 848 × 480, 800 × 600, 720 × 576, 720 × 480, 640 × 480.
POWER CONSUMPTION:	5V DC, 3A max.
OPERATING TEMPERATURE	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
DIMENSIONS:	12.8cm × 2.6cm × 10.9cm (5.05" × 1.02" × 4.29").
WEIGHT:	0.36kg (0.26kg).
INCLUDED ACCESSORIES:	Power supply, power cord, plastic bracket set.