

Kramer KDS-MP2 HD Digital Signage Media Player

I/O CONNECTORS:	1 HDMI, 2 USB 2.0, 1 Ethernet on a RJ-45 connector, 1 unbalanced stereo audio on a 3.5mm mini jack, micro SD card slot.
VIDEO FORMAT SUPPORT:	POP AI Screen Media Standards S6 (MPEG-1 SIF, 3Mbps CBR) S7 (MPEG-1 480p, 10Mbps CBR) S8 (MPEG-1 720p, 15Mbps CBR) S9 (MPEG-2 480p, 6Mbps CBR) S10 (MPEG-2 720p, 12Mbps CBR) S11 (MPEG-4 AVC, 480p, 6Mbps CBR) S12 (MPEG-4 AVC, 720p, 10Mbps CBR) E4 (VC-1/WMV9, MP@ML, 720p) E7 (MPEG-4 ASP, 480p, 10Mbps CBR) E8 (MPEG-4 AVC, 1080p, 10Mbps CBR).
IMAGE FORMAT SUPPORT:	POP AI Screen Media Standards S1 (JPEG 480p baseline) S2 (JPEG 720p baseline) S3 (JPEG 1080p baseline) E1 (PNG 24bpp+alpha, 480p) E2 (PNG 24bpp+alpha, 720p) E3 (PNG 24bpp+alpha, 1080p).
AUDIO CODEC SUPPORT:	POP AI Screen Media Standards S4 (MPEG L2 audio) S5 (MP3 audio, 320Kbps).
DYNAMIC CONTENT:	W3C HTML5 (HTML, CSS, JavaScript) W3C SMIL 3.0 instructions (sub-set).
INDICATORS:	Power(green), Status(orange).
LOCAL STORAGE:	8 GB on-board flash memory (up to 6hrs of typical 720p video @3Mbps) Micro SD card expansion slot.
POWER REQUIREMENT:	12V 1.5A DC.
POWER CONSUMPTION:	6W.
OPERATING TEMPERATURE:	0° to 45°C (32° to 113°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F) .
HUMIDITY:	10 - 85% @40°C, 32° to 104°F non-condensing.
DIMENSIONS:	167mm x 118.8mm x 24.5mm (6.57" x 4.67" x 0.96").
WEIGHT:	0.275kg (0.61lbs).
SAFETY:	UL/FCC/CE/CCC/C-Tick/VCCI certified power supplies.
CERTIFICATIONS:	CE/FCC/VCCI/TELEC/CCC/IC.
INCLUDED ACCESSORIES:	AC adapter, HDMI cable, 4 Velcro (2 sets).
WARRANTY:	One-year limited parts & labor.