

Kramer KW-14 Expandable Wireless HD Extender (Transmitter/Receiver) Kit

INPUT:	1 HDMI connector (KW-14T), internal antenna (KW-14R).
OUTPUT:	1 IR on a 3.5mm mini jack, internal antenna (KW-14T), 1 HDMI connector (KW- 14R).
VIDEO RESOLUTION:	Up to 1080p @60Hz; 8, 10, or 12-bit color depth and VESA up to 1920 x 1080 @60Hz.
FORMATS:	RGB and YCbCr digital video.
MAXIMUM DATA RATE:	6.75Gbps (2.25Gbps per channel).
MAXIMUM PIXEL CLOCK:	148.5MHz.
AUDIO FORMATS:	PCM, Dolby Digital 2/0, Dolby Digital 2/0 Surround, Dolby Digital 5.1, Dolby Digital Surround EX, DTS 2-channel, DTS Digital Surround 5.1, DTS 96/24.
AUDIO RATE:	Digital audio from the HDMI input up to 6Mbps.
IR COMMUNICATION:	Unidirectional, 38 kHz.
TRANSMISSION POWER:	<18dBm conducted (KW-14T), <12dBm per channel conducted (KW-14R).
RECEIVING SENSITIVITY:	-75dBm (KW-14T), -65dBm (KW-14R).
SYSTEM LATENCY:	<1ms.
STANDARDS:	HDMI with Deep Color, x.v.Color™, 3D, CEC; HDCP 2.0—works with sources that support HDCP repeater mode, DVI 1.0.
RF COMMUNICATION FREQUENCY:	5.19 to 5.795GHz (In Japan and Israel operation is limited to the lower bands; 5.15 to 5.25GHz).
UNOBSTRUCTED TRANSMISSION RANGE:	30m (100ft) (KW-14T), 30m (100ft) (KW-14R).
POWER CONSUMPTION:	5V DC 1A (KW-14T), 5V DC 1.2A (KW-14R).
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
COOLING:	Convection, vented.
ENCLOSURE TYPE:	Plastic.
DIMENSIONS:	8.0cm x 10.2cm x 3.6cm (3.15" x 4.02" x 1.42") W, D, H (KW-14T), 9.5cm x 9.5cm x 3.4cm (3.74" x 3.747" x 1.34") W, D, H (KW-14R).
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHS and WEEE.
VIBRATION:	ISTA 1A in carton (International Safe Transit Association).
COMPLIANCE STANDARDS:	CE, c-UL, UL.
EMMISSION STANDARDS:	CE, C-tick, FCC Class B, ICES, VCCI, KC.
INCLUDED ACCESSORIES:	Power supply 5V, 2 HDMI cables 0.9m (2.95ft) PN 2518-0101003, 1 IR Emitter cable PN 3300-500135.