



KRAMER

OSP-MM1

Optical MM 850nm 10G SFP+ Transceiver



OSPMM1 is a fiber optic transceiver for 850nm multimode signals. This standard pluggable SFP+ optical module has two LC connectors for reception and transmission of signals over two strands of multimode optical fiber

FEATURES

Certified Transceiver - Kramer certified, hotpluggable SFP+ optical module, for highquality transmission of 10.2Gbps signal over multimode fiber cables, connecting 2 simplex multimode fiber strands via LC AP/UPC connectors



KRAMER

TECHNICAL SPECIFICATIONS

OPTICAL LINE:	Multimode G.651.1 compliant OFNR fiber
PORTS:	2strand simplex fiber optic LC(PC/UPC) connector. Note: Do not use with LC(APC) cable connectors
MAX. REACH:	3km (1.8 miles) over OM3 MM fiber
NOMINAL PEAK WAVELENGTH:	850nm
MAX. DATA RATE:	10.2Gbps
TRANSMITTER TYPE:	VCSEL
OPTICAL TYPICAL TRANSMISSION POWER:	2.5dBm
OPTICAL TYPICAL MAXIMUM RECEIVER SENSITIVITY:	11.1dBm
OPTICAL TYPICAL MAXIMUM LOSS BUDGET:	8.6dB
STANDARDS COMPLIANCE:	IEEE 802.3ae, SFF8431
LASER SAFETY COMPLIANCE:	Laser Class I
REGULATORY CERTIFICATIONS:	FDA CDRH 21 CFR 1040 and Laser Notice No. 50, UL and CUL EN609502:2007, RoHS6, EMC EN 55022 and EN 55024
POWER CONSUMPTION:	1W
PRODUCT DIMENSION:	1.33cm x 5.70cm x 0.85cm (0.52" x 2.24" x 0.33") W, D, H
PRODUCT WEIGHT:	0.0kg (0.0lbs) approx
SHIPPING DIMENSION:	12.60cm x 8.40cm x 4.10cm (4.96" x 3.31" x 1.61") W, D, H
SHIPPING WEIGHT:	0.1kg (0.1lbs) approx
OPERATING TEMPERATURE:	0° to 70°C
STORAGE TEMPERATURE:	40° to 85°C
HUMIDITY:	5% to 95% RH

