

# Kramer SL-240C Compact 16-Port Master/Room Controller with PoE

## BIDIRECTIONAL PORTS

- 4 RS-232 serial on 3-pin terminal blocks, 4 GPI/O on 2-pin terminal blocks, 1 Ethernet on a RJ-45 connector, 1 mini-USB connector for firmware upgrade

## INPUTS

- 1 built-in IR sensor (for learning)

## OUTPUTS

- 4 IR out and 4 relays on 2-pin terminal block connectors

## INDICATORS

- LED indicator for each port and function

## PROCESSOR SPEED

- 1GHz

## MEMORY

- 512MB RAM, 4GB Flash

## POWER CONSUMPTION

- 5V DC, 2A

## POWER SOURCE

- PoE (for extra power resiliency, connect to the optional 5V DC power supply)

## PRODUCT DIMENSION

- 18.75cm x 11.50cm x 2.54cm (7.38" x 4.53" x 1.00" ) W, D, H

## PRODUCT WEIGHT

- 0.4kg (1.0lbs) approx

## SHIPPING DIMENSION

- 34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05" ) W, D, H

## SHIPPING WEIGHT

- 1.0kg (2.2lbs) approx