

Kramer Tavor 6-O(B) 6.5 inch/On-Wall 2-Way Powered Speakers - Black

- **DESCRIPTION:** 2way powered speaker
- **BUILT-IN POWER AMPLIFIER:** 2 X 50W RMS, 2 X 140W continuous program
- **FREQUENCY RESPONSE:** 45Hz to 20kHz @10dB, 50Hz to 20kHz @3dB
- **WOOFER:** 6.5" polypropylene cone with rubber edge woofer
- **TWEETER:** 1" silk dome tweeter
- **SENSITIVITY:** 85dB SPL, 1W@1m
- **MAX SPL:** Continuous: 100dB, peak:108dB
- **POWER SOURCE:** 90240V AC 50/60Hz
- **IMPEDANCE:** 4
- **CROSSOVER FREQUENCY:** 8kHz
- **DIRECTIVITY FACTOR (Q):** 7.5 averaged 1kHz to 10kHz
- **DIRECTIVITY INDEX (DI):** 8.7dB averaged 1kHz to 10kHz
- **INPUT CONNECTORS:** Line level unbalanced stereo audio on a 3.5mm mini jack, line level balanced stereo audio on a terminal block connector, line level unbalanced stereo audio on left and right RCA connectors
- **OUTPUT CONNECTORS:** Speaker (to connect to the external passive speaker), 3.5mm mini jack line out for optional subwoofer, 3.5mm mini jack loop output
- **DISPERSION COVERAGE:** Vertical: 54 degrees @2000Hz, horizontal:65deg @2000Hz
- **DAMPING FACTOR:** 19 @4/1000Hz
- **S/N RATIO:** 8090dB
- **THD:** 0.15%
- **CONTROLS:** Volume, bass and treble
- **INPUT POWER:** ON or AUTO
- **STANDBY MODE POWER CONSUMPTION:** 0.5W
- **INPUT LEVEL FOR SYSTEM "WAKE-UP" FROM STANDBY MODE:** 12mV
- **MATERIALS:** Aluminum grill, steel brackets, ABS cabinet
- **WEIGHT PER SINGLE SPEAKER:**
 - Active speaker: 3.6kg (7.93lbs) approx
 - Passive Speaker: 2.7kg (5.93lbs) approx
- **WEIGHT WITH MOUNTING KIT:**
 - Active speaker: 4.2kg (9.25lbs) approx
 - Passive Speaker: 3.2kg (7.05lbs) approx
- **SHIPPING WEIGHT** 9.25kg (20.39lbs) approx
- **(FOR PAIR):**
 - **DIMENSIONS:** 21cm x 18.6cm x 30.2cm (8.3" x 7.3" x 11.9") W, D, H
 - **DIMENSIONS with mounting brackets:** 21cm x 25cm x 32cm (8.3" x9.8" x12.6") W, D, H
 - **INSTALLATION CLEARANCE:** 25cm (9.8") front panel to wall (with mounting bracket); 6.3cm (2.5") back panel to wall (with mounting bracket)
 - **OPERATING TEMPERATURE:** 15° to +70°C (5° to 158°F)
 - **STORAGE TEMPERAURE:** 30° to +55°C (22° to 131°F)
 - **HUMIDITY:** 25% to 90%, RHL noncondensing
 - **ACCESSORIES:** 1 pair of Ushaped rotating mounting brackets with 4 mounting knobs, 4m (13.12ft) power cord, 4m (13.12ft) loudspeaker cable, 2m (6.6ft) 3.5mm to 2 RCA cable
 - **COLORS:** Available in white