

Kramer TAVOR 8-T(W) 8 inch High-Performance/Powered Ceiling Tile Speaker/White

DESCRIPTION:	Active flat ceiling speaker.
FREQUENCY RESPONSE:	65Hz to 20kHz @-10dB, 80Hz to 20kHz @±3dB.
WOOFER:	8" (200mm) made with Kevlar® cone with rubber surround.
TWEETER:	Four 0.8" titanium pivoting tweeters.
SENSITIVITY:	87dB 1W @1m.
MAX SPL:	Continuous: 102dB, peak: 105dB.
POWER HANDLING:	40W RMS, 110W continuous program.
CROSSOVER FREQUENCY:	2kHz.
DIRECTIVITY FACTOR (Q):	9.43 averaged 1kHz to 10kHz.
DIRECTIVITY INDEX (DI):	9.5dB averaged 1kHz to 10kHz.
INPUT CONNECTORS:	Terminal block connectors.
CONTROLS:	3 independent input level trimmer, 1 master volume trimmer.
MATERIALS:	Frame, steel grills (595x595mm, 600x600mm), cable holder.
DIMENSIONS:	60cm x 60cm x 10cm (tile size), 59.5cm x 59.5cm x 10cm (tile size) for any region with suspended ceiling tiles of 595mm.
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F).
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F).
HUMIDITY:	10% to 90%, RHL non-condensing.
ACCESSORIES:	24V DC power adapter, 2 available grills (595x595mm, 600x600mm).
COLORS:	Available in white.