

Kramer TBUS-1N(B) Table Mount Modular Multi-Connection Solution/Retractable Lid/Black Anodized Aluminum Top

POWER SOURCE

- Single socket: 100–240V AC 50/60Hz, 5A (Universal, USA, Germany and EU, Belgium and France, Italy, Australia) or 220V AC 50/60Hz, 5A (Israel, South Africa)
- Dual power kit assemblies: 100–240V AC 50/60Hz, 5A (Universal, USA, Germany and EU, France) or 220V AC 50/60Hz, 5A (Israel, South Africa)

FUSE RATING

- T 6.3A 250V

OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

HUMIDITY

- 10% to 90%, RHL non-condensing

STORAGE HUMIDITY RANGE

- 5 to 95% RHL, non-condensing

DIMENSIONS

- 21.4cm x 19.2cm x 13.6cm (8.42" x 7.56" x 5.35") W, D, H

WEIGHT

- TBUS-1N: 2kg (4.4lbs) approx
- accessories (table clamps, metal template and so on): 0.89kg (1.96lbs)

ACCESSORIES

- Six self-locking ties, metal template

OPTIONS

- Inner frames, passive wall plates and interfaces, power socket kits, power cord