

Kramer TBUS-201xl(B) Pop-Up Table Mount Multi-Connection Solution/Black

PORTS:	1 HDMI connector, 1 Ethernet RJ-45 connector, 1 15-pin HD connector, 1 3.5mm mini jack.
POWER SOCKET ASSEMBLIES:	USA 100-220V AC, 50/60Hz, 5A per outlet; Germany and EU 100-240V AC, 50/60Hz, 5A per outlet; Belgium and France 100-240V AC, 50/60Hz, 5A per outlet; Italy 100-240V AC, 50/60Hz, 5A per outlet; Australia 100-240V AC, 50/60Hz, 5A per outlet; Israel 220V AC, 50/60Hz, 5A per outlet; South Africa 220V AC, 50/60Hz, 5A per outlet; Switzerland 220V AC, 50/60Hz, 5A per outlet; UK 220V AC, 50/60Hz, 5A per outlet; Brazil 220V AC, 50/60Hz, 5A per outlet.
OPERATING TEMPERATURE RANGE:	+5° to +45°C (41° to 113°F).
OPERATING HUMIDITY RANGE:	10 to 90% RHL, non-condensing.
STORAGE TEMPERATURE RANGE:	-20° to +70°C (-4° to 158°F).
STORAGE HUMIDITY RANGE:	5 to 95% RHL, non-condensing.
DIMENSIONS:	Including the outer rim: 14.5cm x 13.2cm x 17.3cm (5.71" x 5.2" x 6.81") W, D, H; Without the outer rim: 13.3cm x 12.0cm x 17.3cm (5.24" x 4.72" x 6.81") W, D, H.
WEIGHT:	0.85kg (1.87lbs) approx., 1.2kg (2.65lbs) approx. with mounting brackets.
ACCESSORIES:	Cardboard template.
OPTIONS:	Power socket kits, power cord.