

Kramer TP-780T 4K UHD HDMI/RS-232/IR over HDBaseT Extender (Transmitter) with POE

INPUTS

- 1 HDMI connector

OUTPUTS

- 1 RJ-45 connector

PORTS

- 1 IR on a 3.5mm mini jack, 1 RS-232 on a 9-pin D-sub connector

MAX. DATA RATE

- Supports up to 10.2Gbps (3.4Gbps per graphic channel)

RS-232 BAUD RATE

- 115200

COMPLIANCE WITH HDMI STANDARD

- Supports HDMI and HDCP

POWER CONSUMPTION

- 48V DC, 240mA

OPERATING TEMPERATURE

- 0° to 40°C (32° to 104°F)

STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

HUMIDITY

- 10% to 90%, RHL non-condensing

INCLUDED ACCESSORIES

- Power supply

OPTIONS

- RK-T2B 19" rack mount, Kramer external IR sensor (P/N: 95-0104050), Kramer IR emitter cable (P/N: C-A35/IRE-10)

PRODUCT DIMENSION

- 18.75cm x 11.50cm x 2.54cm (7.38" x 4.53" x 1.00") W, D, H

PRODUCT WEIGHT

- 0.4kg (1.0lbs) approx

SHIPPING DIMENSION

- 34.50cm x 16.50cm x 5.20cm (13.58" x 6.50" x 2.05") W, D, H

SHIPPING WEIGHT

- 1.0kg (2.2lbs) approx