

## ViewZ VZ-DC24-320 Output 24V DC / 320W Power Transformer

<b>FEATURES</b>	
Input Voltage	88 ~ 264V AC /124 ~ 370V DC, 47 ~ 63 Hz
Output Voltage	DC 24V/321.6 W
Output Voltage Adjustment Range	20 -26.4V
Total Output Current / Range	13.4A/0~13.4A
<b>PROTECTION</b>	
Overload Type	105 ~ 135% rated output power Hiccup mode, recovers automatically after fault condition is removed
Over voltage Type	27.6 ~32.4V Shut down o/p voltage. Power Recovery
Over temperature	Shut down o/p voltage. Recovers automatically after temperature goes down
<b>DIMENSIONS &amp; WEIGHT</b>	
Net Dimensions (Width x Height x Length) Gross Dimensions	8.26" x 13.38" x 3.34" / 210 x 340 x 85 mm 11.75" x 17.5" x 7" / 298.45 x 444.5 x 177.8 mm
Net Weight / Gross Weight	8.2 lbs (3.7 kg)/9.7 lbs (4.4 kg)
<b>GENERAL</b>	
Regulations SAFETY STANDARDS	UL/CUL
Operating Humidity	20 ~ 90% RH. Non-condensing
Storage Humidity	10 ~ 95% RH. Non-condensing
Operating Temperature	-22°F ~ 158°F /-30°C ~ +70°C
Storage Temperature	-40°F ~ 185°F /-40°C ~ +85°C
Temperature Coefficient	±0.03%/°C (0°C~50°C)
Vibration	10 ~ 500Hz, 2G 10min./1cycle, 60min. each along X, Y, Z axes
MTBF.	206.5K hrs min. MIL-HDBK-217F (25°C)