

Kramer 861 18G 4K HDR Pocket Signal Generator/Analyzer and Cable Tester

INPUTS

- 1 HDMI: On a female HDMI connector

OUTPUTS

- 1 HDMI: On a female HDMI connector

PORTS

- 1 USB: On a female Micro-B connector

VIDEO

- Max Data Rate: 18Gbps (6Gbps per graphic channel)
- Max Resolution: 4K UHD @60Hz (4:4:4, 8-bit)
- Supported Output Resolutions: 480p@59Hz, 576p@50, 720p@25/30/50/60, 1080i@50/60, 1080p@24/25/30/50/60, 4K(3840×2160p)@24/25/30/50/60, 4K(4096×2160p)@24/25/30/50/60
- Standards Compliance: HDMI 2.0 and HDCP 1.4, 2.2

AUDIO (EMBEDDED) OUTPUT SUPPORT

- LPCM 2.0, 5.1, and 7.1

POWER

- Source: 5V, 2.1A USB Power
- Consumption: 4.7W

ENVIRONMENTAL CONDITIONS

- Operating Temperature: 0° to +40°C (32° to 104°F)
- Storage Temperature: -20° to +50°C (-40° to 158°F)
- Humidity: 20% to 90%, RH non-condensing

REGULATORY

- Safety: CE, FCC
- Environmental: RoHs, WEEE
- ESD Protection: Human body model — ±12kV (Air Discharge), ±8kV (Contact Discharge)

ENCLOSURE

- Type: Metal
- Cooling: Convection Ventilation

ACCESSORIES

- Included: Micro-B USB cable, 1 C-HM/HM/PICO/BK-3 cable, 1 lithium-ion 3.6V/3200maH rechargeable battery, belt pouch

PRODUCT DIMENSION

- 8.00cm x 14.00cm x 2.70cm (3.15" x 5.51" x 1.06") W, D, H

PRODUCT WEIGHT

- 0.3kg (0.6lbs) approx

SHIPPING DIMENSION

- 24.80cm x 18.80cm x 5.40cm (9.76" x 7.40" x 2.13") W, D, H

SHIPPING WEIGHT

- 0.6kg (1.4lbs) approx