

Kramer DTAXR-IN4-F32 4-Channel 4K60 4x2x0 HDMI over Extended Reach HDBaseT Input Card with Selectable Embedded or De-embedded Analog Audio

INPUTS

- 4 HDBaseT TP on RJ45 connectors
- 4 Unbalanced audio on a 16 pin terminal block

PORTS

- 4 RS-232 Serial ports, 4 IR ports and 1 Ethernet port on an RJ-45 connector

BANDWIDTH PER CHANNEL

- Video: 3.4Gbps
- Serial data: 115200

TOTAL BANDWIDTH

- Video: 10.2Gbps
- Serial data: 115200

MAXIMUM RANGE

- Up to 100m at normal mode (4K), up to 130m (430ft) at normal mode (2K), up to 180m (590ft) ultra mode (1080p @60Hz @24bpp) when using BC-UNIKAT cables

3D PASS THROUGH

- Supported

POWER CONSUMPTION

- 34W

OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

HUMIDITY

- 10% to 90%, RHL non-condensing

STANDARD COMPLIANCE

- HDCP 1.4, HDMI 1.3a, HDBaseT

SAFETY REGULATORY COMPLIANCE

- CE

ENVIRONMENTAL REGULATORY COMPLIANCE

- Complies with appropriate requirements of RoHs and WEEE

PRODUCT DIMENSION

- 22.00cm x 18.80cm x 2.00cm (8.66" x 7.40" x 0.79") W, D, H

PRODUCT WEIGHT

- 0.5kg (1.1lbs) approx

SHIPPING DIMENSION

- 25.00cm x 22.50cm x 5.50cm (9.84" x 8.86" x 2.17") W, D, H

SHIPPING WEIGHT

- 0.7kg (1.5lbs) approx