

# Kramer DTAxr-OUT2-F16 2-Channel 4K60 4x2x0 HDMI over Extended Reach HDBaseT Output Card with Selectable Embedded or De-embedded Analog Audio

## OUTPUTS

- 2 HDBaseT TP on RJ45 connectors

## PORTS

- 2 RS-232 Serial ports, 2 IR ports and 2 Unbalanced audio on a 16 pin terminal block, 1 Ethernet port on an RJ-45 connector

## BANDWIDTH PER CHANNEL

- Video: 3.4Gbps
- Serial Data: 115200

## TOTAL BANDWIDTH

- Video: 10.2Gbps
- Serial Data: 115200

## MAXIMUM RANGE

- Up to 100m at normal mode (4K), up to 130m (430ft) at normal mode (2K), up to 180m (590ft) ultra mode (1080p @60Hz @24bpp) when using BC-UNIKAT cables

## 3D PASS THROUGH

- Supported

## POWER CONSUMPTION

- 13W

## OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

## STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

## HUMIDITY

- 10% to 90%, RHL non-condensing

## STANDARD COMPLIANCE

- HDCP 1.4, HDMI 1.3a, HDBaseT

## SAFETY REGULATORY COMPLIANCE

- CE

## ENVIRONMENTAL REGULATORY COMPLIANCE

- Complies with appropriate requirements of RoHs and WEEE

## PRODUCT DIMENSION

- 19.00cm x 13.00cm x 2.00cm (7.48" x 5.12" x 0.79" ) W, D, H

## PRODUCT WEIGHT

- 0.2kg (0.5lbs) approx

## SHIPPING DIMENSION

- 24.20cm x 16.80cm x 6.00cm (9.53" x 6.61" x 2.36" ) W, D, H

## SHIPPING WEIGHT

- 0.3kg (0.7lbs) approx