



KRAMER

DTAxr-OUT4-F32

4-Channel 4K60 4:2:0 HDMI over Extended Reach HDBaseT Output Card with Selectable Embedded or De-embedded Analog Audio

| Ethernet - RJ-45 | HDCP Compliant
| Kramer Core | HDBaseT



DTAxrOUT4F32 is a fourchannel HDMI, analog audio, bidirectional RS232, Ethernet, & IR over HDBaseT twisted pair transmitter card for the VS3232 Series Modular MultiFormat Digital Matrix Switchers. The DTAxrOUT4F32 outputs four extended reach HDBaseT signals with analog audio, bidirectional RS232, IR, and Ethernet from the chassis to the line

FEATURES

Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel)

HDBaseT Technology - HDTV compatible, HDCP compliant

3D Pass-Through

System Range - Up to 130m (430ft) normal mode; up to 180m (590ft) ultramode (1080p @60Hz @24bpp)



TECHNICAL SPECIFICATIONS

OUTPUTS	4 HDBaseT TP on RJ45 connectors, 4 Balanced audio on terminal block connectors, 4 RS232 Serial ports and 4 IR ports on 2 10 pin terminal blocks, 1 Ethernet port on an RJ45 connector
BANDWIDTH PER CHANNEL:	Video: 2.25Gbps; Serial Data: 115200
TOTAL BANDWIDTH:	Video: 6.75Gbps; Serial Data: 115200
MAXIMUM RANGE:	130m (430ft) normal mode, 180m (590ft) ultramode (1080p @60Hz @24bpp)
3D PASS THROUGH:	Supported
POWER CONSUMPTION:	26W
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL noncondensing
PRODUCT DIMENSION:	22.00cm x 18.80cm x 2.00cm (8.66" x 7.40" x 0.79") W, D, H
PRODUCT WEIGHT:	0.4kg (0.9lbs) approx
SHIPPING DIMENSION:	25.00cm x 22.50cm x 5.50cm (9.84" x 8.86" x 2.17") W, D, H
SHIPPING WEIGHT:	0.6kg (1.2lbs) approx
STANDARD COMPLIANCE:	HDCP 1.4, HDMI 1.3a, HDBaseT
SAFETY REGULATORY COMPLIANCE:	CE
ENVIRONMENTAL REGULATORY COMPLIANCE:	Complies with appropriate requirements of RoHs and WEEE