

# Kramer DTAXR-OUT4-F32 4-Channel 4K60 4x2x0 HDMI over Extended Reach HDBaseT Output Card with Selectable Embedded or De-embedded Analog Audio

## OUTPUTS

- 4 HDBaseT TP on RJ45 connectors, 4 Balanced audio on terminal block connectors, 4 RS-232 Serial ports and 4 IR ports on 2 10 pin terminal blocks, 1 Ethernet port on an RJ-45 connector

## BANDWIDTH PER CHANNEL

- Video: 2.25Gbps
- Serial Data: 115200

## TOTAL BANDWIDTH

- Video: 6.75Gbps
- Serial Data: 115200

## MAXIMUM RANGE

- 130m (430ft) normal mode, 180m (590ft) ultra-mode (1080p @60Hz @24bpp)

## 3D PASS THROUGH

- Supported

## POWER CONSUMPTION

- 26W

## OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

## STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

## HUMIDITY

- 10% to 90%, RHL non-condensing

## STANDARD COMPLIANCE

- HDCP 1.4, HDMI 1.3a, HDBaseT

## SAFETY REGULATORY COMPLIANCE

- CE

## ENVIRONMENTAL REGULATORY COMPLIANCE

- Complies with appropriate requirements of RoHs and WEEE

## PRODUCT DIMENSION

- 22.00cm x 18.80cm x 2.00cm (8.66" x 7.40" x 0.79" ) W, D, H

## PRODUCT WEIGHT

- 0.4kg (0.9lbs) approx

## SHIPPING DIMENSION

- 25.00cm x 22.50cm x 5.50cm (9.84" x 8.86" x 2.17" ) W, D, H

## SHIPPING WEIGHT

- 0.6kg (1.2lbs) approx