

Kramer GALIL 6-AW (BLACK) 6.5 inch 2-way All-purpose on-wall mounting speakers/65Hz to 20kHz/Black

DESCRIPTION

- 2-way on-wall speakers

FREQUENCY RESPONSE

- 65Hz to 20kHz @-10dB, 80Hz to 20kHz @±3dB

WOOFER

- 6.5" (165mm) polypropylene cone with rubber surround

TWEETER

- 1" (25mm) silk dome

IMPEDANCE

- 8Ω (transformer tap in off position)

TRANSFORMER TAPS

- 70V — 30W/15W/7.5W/3.7W/Off (Lo-Z), 100V — 30W/15W/7.5W/Off (Lo-Z)

SENSITIVITY

- 87dB SPL, 1W @1m

MAX SPL

- Continuous: 102dB, peak: 105dB

POWER HANDLING

- 40W RMS, 110W continuous program

CROSSOVER FREQUENCY

- 4.3kHz

DIRECTIVITY FACTOR (Q)

- 3.9 averaged 1kHz to 10kHz

DIRECTIVITY INDEX (DI)

- 5.9dB averaged 1kHz to 10kHz

INPUT CONNECTORS

- Terminal blocks

MATERIALS

- Frame, aluminum grill, steel brackets and ABS cabinet

STANDARDS COMPLIANCE

- IP66 compliant

OPERATING TEMPERATURE

- 0° to +40°C (32° to 104°F)

STORAGE TEMPERATURE

- -40° to +70°C (-40° to 158°F)

HUMIDITY

- 10% to 90%, RHL non-condensing

WEIGHT PER SINGLE SPEAKER

- 2.8kg (6.2lbs) approx

WEIGHT WITH MOUNTING KIT

- 3kg (6.6lbs) approx

SHIPPING WEIGHT (FOR PAIR)

- 6.6kg (14.6lbs) approx

DIMENSIONS WITH MOUNTING BRACKETS

- 21.5cm x 22.5cm x 30.1cm (8.5" x 8.9" x 11.9"), W, D, H

INSTALLATION CLEARANCE

- Front panel to wall (with mounting bracket): 22.7cm (8.9"), back panel to wall (with mounting bracket): 3.8cm (1.5")

ACCESSORIES

- 2 mounting brackets (including 4 knobs and 4 mounting screws)

OPTIONS

- BCP-2S speaker cable

COLOR

- Black